



# Multicore Speaker Cables

All **eurocable** speaker cables are flame resistant and known for their extreme flexibility due to the very high strand count of individual conductors. Speaker cables are designed with no center conductor attributing to their superior strength in field applications where long hanging lengths are required. All channel pairs are clearly labeled and arranged using our unique production process to ensure identical distance to the red (+) and black (-) conductors.



CVS LKCode	04N25	04N40	06N25	06N40	08N25	08N40	16N40	24N40	
<b>GENERAL DATA</b>									
Cable	O.D.	11.10 mm	13.20 mm	14.20 mm	15.50 mm	16.00 mm	19.50 mm	21.50 mm	26.80 mm
	Standard reels	200 m						152 m	200 m
	Weight Kg/100m	21.50	34.50	35.00	47.60	47	65.50	93.90	140.00
Operating temperature 5°C/+70°C									
Jacket	Material PVC fire resistant								
	Nominal Thickness	≥ 1.20 mm	≥ 1.80 mm	≥ 1.60 mm	≥ 1.50 mm	≥ 1.60 mm	≥ 1.80 mm	2.20 mm	
Conductor	D.C.R. [ ohm/km ] at 20° C	8	5	8	5	8	5		
	Quantity	4		6		8		16	24
	Strand	80 x 0.2 mm	128 x 0.2 mm	80 x 0.2 mm	128 x 0.2 mm	80 x 0.2 mm	128 x 0.2 mm	80 x 0.2 mm	128 x 0.2 mm
	Area/AWG	2.50 mm <sup>2</sup> /13	4.00 mm <sup>2</sup> /11	2.50 mm <sup>2</sup> /13	4.00 mm <sup>2</sup> /11	2.50 mm <sup>2</sup> /13	4.00 mm <sup>2</sup> /11	4.00 mm <sup>2</sup> /11	
	Insul. O.D.	3.4	4.0	3.4	4.0	3.4	4.0	4.0	3.6
Material PVC fire resistant									


**Speaker cable with Neutrik speakONconnectors** SIGNAL INTEGRITY

<p><b>S41FX425</b> </p> <p>Speaker cable 4x2.5 mm<sup>2</sup> wired with Neutrik speakON 50A connectors</p>	<p><b>S41FT425</b> </p> <p>Speaker cable 4x2.5 mm<sup>2</sup> wired with Neutrik speakON 50A connectors Metal</p>	<p><b>S81FC840</b> </p> <p>Speaker cable 8x4 mm<sup>2</sup> wired with Neutrik speakON connectors</p>
<p><b>S41FX440</b> </p> <p>Speaker cable 4x4 mm<sup>2</sup> wired with Neutrik speakON 50A connectors</p>	<p><b>S41FT440</b> </p> <p>Speaker cable 4x4 mm<sup>2</sup> wired with Neutrik speakON 50A connectors Metal</p>	<p><b>S81FT840</b> </p> <p>Speaker cable 8x4 mm<sup>2</sup> wired with Neutrik speakON connectors Metal</p>

\* Length (meters): **3 5 10 15**       With packaging, no heat shrink       No packaging, with heat shrink  
 Feet       Meters       No packaging, no heat shrink       With packaging and heat shrink


# Multicore Speaker Cables

Today's professional line arrays require more granular control in order to effectively leverage high-density power amplifiers and DSP control. The **eurocable** series of multicore speaker cables, and LK multi-conductor speaker connectors, were specifically designed for touring applications and are available in 4, 8, 16, 24, 36 and 48 conductor configurations. The CVS LK36N40AD2 and LK48N40AD2 also contain digital pairs to transport common laser and inclinometer signals.



CE

MOBILE
JACKET COLOR <span style="display:inline-block; width:10px; height:10px; background-color:black;"></span>
92 m/300 feet ON WOODEN REELS



GENERAL DATA		CVS LK36N40AD2*	CVS LK48N40AD2*	Speaker	Audio
Cable	O.D.	≤ 31.10 mm	≤ 35.00 mm	3.60 mm	1.20 mm
	Standard reels	92 m			
	Weight Kg/100m	197	257	-	
	Operating temperature	-20° C/+70° C			
Jacket	Material	PVC			
	Nominal Thickness	2.10 mm		1.00 mm	0.60 mm
Shield	Material	-			Aluminium - Polyester foil + tinned copper drain wire 7 x 0.16 mm
	Coverage	-			
Conductor	Qty	-		36 (36N40AD2) 48 (48N40AD2)	2
	Strand	-		128 x 0.20 mm	7 x 0.16 mm
	Area/AWG	-		4.00 mm <sup>2</sup> /11	0.14 mm <sup>2</sup> /26
	Insul. O.D.	-		3.60 mm	1.20 mm
	Material	-		Annealed bare copper PVC insulated	Annealed tinned copper polyolefine insulated

\*on request